HP DesignJet XL 3600 Multifunction Printer series



Experience a new standard with the most immediate and robust MFP in the market²



IMMEDIATE RESULTS—Fastest first page out²

- Don't wait in front of your printer with the fastest first page out, in just 29 seconds.²
- Free up your time with radically simple and fast batch PDF printing using HP Click software.
- Quickly access your personal and group folders from the touchscreen, so you can print and share right away.³
- Easily digitise your projects with automated scanning, user-centric quicksets, and postediting capabilities.

A NEW STANDARD—Experience extreme reliability

- Built with the most robust design for demanding environments.²
- Best fit for your office with up to 30% smaller footprint and the most quiet operation.⁴
- Flawless user experience thanks to automatic media loading and print stacking up to 100 pages.
- Get the lowest running costs, with mono and colour prints at the same price and using up to 10X less energy.²

SECURE—World's most secure large-format printer¹

- Rely on the best network protection with features like HP Secure Boot and whitelisting.¹
- Control who accesses the printer and its confidential documents with secure user authentication.
- Keep your fleet secure at any time with HP JetAdvantage Security Manager.

For more information, please visit http://www.hp.com/go/designjetxl3600

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Advanced embedded security features are based on HP review of 2019 published embedded security features of competitive printers, as of February 2019.

² Based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 70% of the share of low-volume LED printers in the US and Europe according to IDC

Eased on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 70% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Fastest first page out and up to 10 times less energy consumption based on internal HP testing for specific use scenarios. Operational costs based on low-volume LED technology under \$17,000 USD in the market as of November, 2018. Operational costs consist of supplies and service costs. For testing criteria, see http://www.hp.com/go/designjetxlclaims.

 ³ Using Lightweight Directory Access Protocol (LDAP).
 ⁴ 30% smaller footprint based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 40% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Measure done considering operational footprint (with the media drawer open). Most quiet operation based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 70% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Most quiet according to internal HP testing of operation mode and ready/sound mode sound pressure (plain paper, line drawing, normal mode) compared to published specifications of competitive printers. For testing criteria, see http://www.hp.com/go/designjetxlclaims.

Technical specifications

Р	ri	n	t	

horzontal cutter Scamer Stage 10 x 279 to 914-x movieth, up to 200-m length, 3-in core (default) or 2-in core (applications) Stendard sheets A4, A3, A2, A1, A0, (A, B, C, D.) Scammage 60 to 328 g/m² Thickness Up to 5 m this pto 19 3 m thi	Print	
Print resolution 193 An Entire Management of the Committee of the Committ	First page out	29 sec; Wake-up time less than 10 sec (no warm-up time)
Post paragraphy Space 1200 patrimode day	Print speed	
Pietr enclation ID 19 2-400 x 1200 optionsed dys Fechnology IP Themat shipte Dys-based CG, M, M, CR, DC, 90 fm/O Init deep Init Area Init Area Init Area ID 16 (K, M, CR, DC) 9 fm/O Init Area ID 16 (K, M, CR, DC) 9 fm/O Init Area ID 16 (K, M, CR, DC) 9 fm/O Init Area ID 16 (K, M, CR, DC) 9 fm/O Init Area ID 16 (K, M, CR, DC) 9 fm/O Init Area Init Area ID 16 (K, M, CR, DC) 9 fm/O Init Area Init		
INCHARDORY INCHARDORY Dys-Landed (C. G., M, pl. V.): prigment-based (mil) in drop Spit (C. M., V., C., Mr.): pil (mil) Firithecids 1 (C. M., V., Mr.): pil (mil) Multimutorio capabilities Scan speed Scan the 37 E2 creduct clause 200 data up to 25 d. creduct (proyected 200 data) Multimutorio capabilities Scan speed Scan the 37 E2 creduct clause 200 data up to 25 d. creduct (proyected 200 data) Scan teschalation Up to 600 dis Hospital (D. S.): pil (mil) (2.5 d. creduct) Scan teschalation Up to 600 dis Hospital (D. S.): pil (mil) (1.5 d. creduct) Scan teschalation JPE, IFF, PDF (for PostScript Printer) Scan destinations USS shared moves he folder, printer HDD, small Media Sheet sees 2 10 to 279 to 91 dis 4 t. 219 mm Reduction (S. M.): pil (mil) (1.5 d. creduct) Scan teschalation Sheet sees 2 10 to 279 to 91 dis 4 t. 219 mm Reduction (S. M.): pil (mil) (1.5 d. creduct) Scan teschalation ARA ARA ARA, ROJE, B. C. D. D. Germmanya Go 10 dis 28 giner Scan Scan Scan Scan Scan Scan Scan Scan	Drint resolution	
institypes Operated IC. G. M. pt. N. you price bissed (m)		
indication Financial CLE, M. Y. G., CRE, D. J. (M. M.) Financial CLE, C.		-
Printenses 1.16, N.Y.C. emit, plot 7, 22 cm/sec (colour, 2001 dpl), up to 2.54 cm/sec (grapscale, 2001 dpl) Copy. Up to 1.524 cm/sec (colour, 2001 dpl), up to 2.54 cm/sec (grapscale, 2001 dpl) Copy. Up to 1.524 cm/sec (colour, 2001 dpl), up to 2.54 cm/sec (grapscale, 2001 dpl) Copy. Up to 1.524 cm/sec (colour, 2001 dpl), up to 2.54 cm/sec (grapscale, 2001 dpl) Copy. Up to 1.524 cm/sec (colour, 2001 dpl), up to 2.54 cm/sec (grapscale, 2001 dpl) Copy. Up to 1.524 cm/sec (colour, 2001 dpl), up to 2.54 cm/sec (grapscale, 2001 dpl) Copy. Up to 1.524 cm/sec (colour, 2001 dpl), up to 2.54 cm/sec (grapscale, 2001 dpl) Madriannous consistence Scan destinations O.B. mem. Scan destinations US\$, Sheed relevor's (blobs; printer IPD), email Media Handling Sheet level, a cateroidic front-loading poll feed, smart roil switching ² , integrated output studes; media bin, automatic horizontal output and studes; media bin, automatic horizontal output studes; media bin, automatic horizontal properties of the students of the students of the students output studes; media bin, automatic horizontal properties of the students of the studen	Ink types	
Line accoratory 40.1967 Martimenton in wellth Audifunction capabilities San speed Sant Lip to 7.6.7 or overse (circulor, 200 clips), up to 2.5.4 cm/sec (grapscale, 200 clips) Copy. Up to 1.52 cm/sec (circulor, 200 clips), up to 2.5.4 cm/sec (grapscale, 200 clips) Copy. Up to 1.52 cm/sec (circulor, 200 clips), up to 2.5.4 cm/sec (grapscale, 200 clips) Copy. Up to 1.52 cm/sec (circulor, 200 clips), up to 2.5.4 cm/sec (grapscale, 200 clips) Copy. Up to 1.52 cm/sec (circulor, 200 clips), up to 2.5.4 cm/sec (grapscale, 200 clips) Copy. Up to 1.50 cm/sec (grapscale, 200 clips) Discontinuous Sec (grapscale, 200 clips) Sheet sec (grapscale, 200 clips) Copy. Up to 1.5 cm/sec (grapscale, 200 clips) Sheet sec (grapsca	Ink drop	6 pl (C, M, Y, G, pK); 9 pl (mK)
Martinardion capabilities Same tup to 7.62 cm/sec (capus, 200 dp), up to 25.4 cm/sec (grayscale, 200 dp) Copy. Up to 15.24 cm/sec (capus, 200 dp), up to 25.4 cm/sec (grayscale, 200 dp) Copy. Up to 15.24 cm/sec (capus, 200 dp), up to 25.4 cm/sec (grayscale, 200 dp) Copy. Up to 15.24 cm/sec (capus, 200 dp), up to 25.4 cm/sec (grayscale, 200 dp) Copy. Up to 15.24 cm/sec (capus, 200 dp), up to 25.4 cm/sec (grayscale, 200 dp) Copy. Up to 15.24 cm/sec (capus, 200 dp), up to 25.4 cm/sec (grayscale, 200 dp) Copy. Up to 15.24 cm/	Printheads	1 (C, M, Y, G, mK, pK)
Scan speed Scan: Up to 7,62 cm/sec (coloux, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi)	Line accuracy	±0.1% ²
Scene Up to 7.52 cm/sec (coloux, 200. dol). up to 25.4 cm/sec (paysociae, 200. dol). Scene resolution Up to 600 dol Maximum scan size 914 x 8000 mm (PEG), 610 x 15.000 mm (TEF), 914 x 8000 mm (PEF); Thickness 0.8 mm 3.00	Minimum line width	0.02 mm (HP-GL/2 addressable);
Scene Up to 7.52 cm/sec (coloux, 200. dol). up to 25.4 cm/sec (paysociae, 200. dol). Scene resolution Up to 600 dol Maximum scan size 914 x 8000 mm (PEG), 610 x 15.000 mm (TEF), 914 x 8000 mm (PEF); Thickness 0.8 mm 3.00	Multifunction capabilities	
Copy Up to 15-24 cm/sec (adout, 200 dpl), up to 25.4 cm/sec (grayscale, 200 dpl) Maximum scan size 914 x 8000 mm (PEC), E10 x 15,000 mm (TEF), 914 x 8000 mm (PEF); Thickness 0,8 mm; San destinations USB, shared network folder, printer HBD, email Media Media Sheet feed, automatic front-loading roll feed, smart roll switching*, integrated output stacker, media bin, automat horizontal cutter Some statistics Sheet size 210 x 279 to 914 x 1219 mm Sheet size 210 x 279 to 914 x 1219 mm Some statistics Sheet size 210 x 279 to 914 x 1219 mm Sheet size 210 x	<u>·</u>	Scan: Up to 7.62 cm/sec (colour 200 doi) up to 25.4 cm/sec (gravecale 200 doi)
Maximum scan size 914 x 8000 mm (MPEQ), 610 x 15,000 mm (MPEP), 914 x 8000 mm (MPOP);	ocan speed	
Thickness 0.8 mm; San format PREC, TRE PEP Flor Por PostScript Printer PDD, email Media Handling Sheet Feed, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll feed, roll feed, s	Scan resolution	Up to 600 dpi
Thickness 0.8 mm; San format PREC, TRE PEP Flor Por PostScript Printer PDD, email Media Handling Sheet Feed, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, meda bin, automatic front-loading roll feed, smart roll feed, roll feed, s	Maximum scan size	914 x 8000 mm (IPEG): 610 x 15,000 mm (TIFF): 914 x 8000 mm (PDF):
Scan desirations USB, shared network folder, printer HDD, email Media Nanding Sheet feet automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, media bin, automatic scanners straight-through scan paper path for sheet and cardboard originals Sheet size 210 x 279 to 914 x 1219 mm Roll size 271 to 1914 x 1219 mm Roll size 273 to 1914 x 1219 mm Roll size 275 to 1914 x 1219 x 1		
Media		
Heading Sheet feed, automatic front-loading roll feed, smart roll switching ¹ , integrated output stacker, media bin, automatic forces of the processing of		
Sheet size automatic front-loading roll feed, smart roll switching?, integrated output stacker, media bin, automatic between class and cathe incomment class in the property of the property o	Scan destinations	USB, shared network folder, printer HDD, email
horizontal cutter Scanner Straight Hirough scan paper path for sheet and cardboard originals Sheet size 210 x 279 to 914-m width, up to 200-m length, 3-in core (default) or 2-in core (optional) Standard sheets A4, A3, A2, A1, A0 (A, B, C, D, B) Grammage 610 328 g/m² Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings, Maps; Orthophotos, Presentations, Renderings Memory 128 G6 fflie processings* Hard disk Standard, Solo G6 (AES-256 encrypted) Connectivity Interfaces Glipble Etherner (1000Base-1), supporting the following standards: TCPIP BootPPDHCP (PP4 only), DHCP46, TFF, PFF, PFF, PFF, PFF, PFF, PFF, PFF	Media	
Sheet Size 279 to 914 x 1219 mm Roll size 279 to 914 x mm width, up to 200-m length, 3-in core (default) or 2-in core (optional) Standard sheets AA, A3, A2, A1, A0 (A, B. C. D. E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (Up to 19.7 mil) Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings Massis Orthopholosis, Presentations, Renderings Memory 128 GB (file processing)* Hard disk Standard, 500 GB (AES-256 encrypted) Connectivity Interfaces Gigabit Ethernet (1000Base-17), supporting the following standards: TCP/IR BootP/DHCP (IPv4 only), DHCPv6, TFTI (IPv4 only), SMPP (v1 v. v2c. v3), Applie Bonique Compatible, W5 Discovery, Embedded Web Server HTTP, HTTPS, IR SMPT Jeranal, Rows IP printing (1000, IPv. IPv8, W5 pinn, NT, INV. v2, SMP3, Satz ITv3, East, X matheritational for 19.4 (V1 v. v2c. v3), Applie Bonique Compatible, W5 Discovery, Embedded Web Server HTTP, HTTPS, IR SMPT Jeranal, Rows IP printing (1001, IPv. IPv8, W5 pinn, NT, INV. v2, SMP3, Satz ITv3, East, X matheritational (1001, IPv8, I	Handling	
Roll size 279 to 914-mm width, up to 200-m length, 3-in core (default) or 2-in core (optional) Standard sheets AA, A3, A2, A1, A0, A, B, C, D, E) Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings, Maps, Orthophotos, Presentations; Renderings Memory 128 GB (Bite processing)* Hard disk Standard, SO GB (AES-256 encrypted) Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IR BootP/DHCP (BPv4 only), DHCPv6, TFFT (BPv4 only), SNMP (V1, V2, V3), Applie Bonique Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Iff (BPv4 only), SNMP (V1, V2, V3), Applie Bonique Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Iff (BPv4 only), SNMP (V1, V2, V3), Applie Bonique Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Iff (BPv4 only), SNMP (V1, V2, V3), Applie Bonique Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Iff (BPv4 only), SNMP (V1, V2, V3), Applie Bonique Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Iff (BPv4 only), SNMP (V1, V2, V3), Applie Bonique Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Iff (BPv4 only), SNMP (V1, V2, V3), Applie Bonique Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), Iff (BPv4 only), DEVER (V1, V3, V4, V4, V4, V4, V4, V4, V4, V4, V4, V4		
Standard sheets A4, A3, A2, A1, A0 (A, B, C, D, E) Grammage 60 to 328 g/m² Finkiness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings, Maps; Orthophotos; Presentations, Renderings Memory 128 GB (Rie processing)*, Hard disk Standard, Stor GB (ABE-2-56 encrypted) Connectivity Interfaces Gligabit Ethernet (1000Base-17, supporting the following standards: TCP/R BootP/IDHC (PuPvd only), DHCPA, TTF (PVd only), SMPP (v1 v2 v3), Aprile Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IF SMPP (Premail), Raw IP printing (9100), IPD, IPP, WS print, NTLM v2; SMBv3, SSL/TLS, 902.1X authentication (LEAP, PEAR, EAF-TLS), DFS Print languages (standard) PostScript Printer Adobe PostScript 3, Adobe PDF 1.7, HP-GL/Z, HP-RTL, TEF, IPPE, CALS G4 Print languages (standard) Non-PostScript Printer Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP PostScript Printer Adobe PostScript in Print from network shared folder, email printing, HP driver for Windows, HP PostScript Printer PostScript Pr		
Grammage 60 to 328 g/m² Thickness Up to 0.5 mm (Up to 19.7 mil) Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings, Maps; Orthophotos; Presentations; Renderings Memory 128 GB file processing!* Hard disk Standard, 500 GB (RES-256 encrypted) Connectivity Interfaces Glapable Ethernet (1000Base-IT), supporting the following standards: TCP/IR BootP/DHCP (IPv4 only), DHCPv6, FTFI (IPv4 only), SNMP (Print), V.R.V., v33, Applie Boniquer Compatible, MS Discovery, Embedded Web Server HTTP, HTTPS, IF SMTP (emails, Raw IP) printing (1010), UP, IPv8, WS print, NTLM v2, SMM3, SSL/TLS, 502.1X authentication (IPv8 only), SNMP (Print), SMTP (emails, Raw IP) printing (1010), UP, IPv8, WS print, NTLM v2, SMM3, SSL/TLS, 502.1X authentication (IPV8 only), IPv8, I		
Thickness Up to 0.5 mm (Up to 19.7 mil) Applications Line drawings, Maps, Orthophotos, Presentations; Renderings Memory 128 GB (Rib processing)*, Hard disk Standard, 500 GB (ASS-256 encrypted) Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP BootP/DHCP (IPV4 only), DHCPv6, TFTI (IPV4 only), SMMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IE SMTP Pernall, Raw IP printing (1910d), IPO, IPP, WS print, NTLM v2, SMRv3, SSL/TLS, 802.1X authentication (LEAP, PEAR, EAPH-LS), DTS PFInt languages (standard) POSSCript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4; Non-PostScript Printer PostScript Printer P	Standard sheets	A4, A3, A2, A1, A0 (A, B, C, D, E)
Applications Line drawings, Maps, Orthophotos, Presentations, Renderings	Grammage	60 to 328 g/m²
Memory 128 GB (file processing)**.	Thickness	Up to 0.5 mm (Up to 19.7 mil)
Flant disk Standard, 500 GB (AES-256 encrypted)	Applications	Line drawings; Maps; Orthophotos; Presentations; Renderings
Flant disk Standard, 500 GB (AES-256 encrypted)	Memory	128 GB (file processing) ⁴ :
Connectivity Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TC9/IB BootP/DHCP (IPv4 only), DHCPv6, TFT (IPv4 only), SNMP (v1, v2c, v2), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTR HTTPS), IF SNMT (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, BEAP_TLS), DES. Print languages (standard) PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, Non-PostScript Printer (HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4) Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP PostScript Printer: PostScript printer (adobe PostScript 3), Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP PostScript Printer: PostScript and PDF Windows, AirPrint for macOS and Android, HP SmartStream (optional) Drivers PostScript Printer: PostScript and PDF Windows, AirPrint for macOS. Security features HP Secure Boot, Whitelstring, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPV3, HTTP Scrue-PIP, Ples-Effrewall, Certificates management, 802.17, XLS 1.0.1.1.11, LP, Web beladmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD S220.22-M), Secure File erase, self-encryptin HDD, encrypted PN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Weight Printer Single-roll: 202 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 170 kg Ship		
Interfaces Gigabit Ethernet (1000Base-T), supporting the following standards: TCPIR BootP/DHCP (IPv4 only), DHCPv6, TFTI (IPv4 only), SMMP (v1, v2c, v3), Apple Bonjour Compabble, W5 Discovery, Embedded Web Server (HTTPH LTTS), SMTP (Jemani), Rav IP printing (1010), IPv, PW Sprint, NTAW, 2-SMBv3, SSL/TLS, 802.1 X authentication (LEAP, PEAR, LEAP-TLS), IPS Print languages (standard) PostScript Printer, Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, IPEG, CALS G4, Non-PostScript Printer, Adobe PostScript 3, Adobe PDF 1.7 Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP P Service for Android, HP Smart App for it and Adroid, HP Smart Stream (optional) Drivers PostScript Printer: PostScript American (PDF Windows drivers, raster drivers for Windows, AirPrint for Chrome OS, HP Click, HP Smart App for it and Adroid, HP Smart Stream (optional) Printing paths Frequency Printer: PostScript American (PDF Windows drivers, raster drivers for Windows, AirPrint for Chrome OS, HP Click, HP Smart App for it and American (PDF Windows AirPrint for Chrome OS, HP Click, HP Smart App for it and American (PDF Windows AirPrint for Chrome OS, HP Click, HP Smart App for it and American (PDF Windows AirPrint for Chrome OS, HP Click, HP Smart App for it and American (PDF Windows AirPrint for Chrome OS, HP Click, HP Smart App for it and American (PDF Windows AirPrint for Chrome OS, HP Click, HP Smart App for it and American (PDF Windows AirPrint for Chrome OS, HP Click, HP Smart App for it and PDF Windows AirPrint for Chrome OS, HP Click, HP Smart App for it and PDF Windows, AirPrint for Chrome OS, HP Click, HP Smart App for it and PDF Windows, AirPrint for Chrome OS, HP Click, HP Smart App for Manager (PDF Windows Air App		Statistical di Social Spices
(If-vid only), SNMP (v1, v2c, v3), Appile Bonijour Compatible, WS Discovery, Embedded Web Server (HTTP HTTPS), ISMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-LS), DFS Print languages (standard) PoStGript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 HP-GL/2, HP-RTL, TI		
HP-GLI/2, HP-RTL, TIFF, JPEG, CALS G4 Printl languages (optional) Non-PostScript Printer: Adobse PostScript 3, Adobse PDF 1.7 Printing paths	Interfaces	
Printing paths Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP P Service for Android, Apple AirPrint driver for macOS and IOS, HP Print for Chrome OS, HP Click, HP Smart App for it and Android, HP SmartStream (optional) Drivers PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AirPrint for macOS Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTP Secure-IPP, IPSec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdwantage Security Manager compatible, Secure bisk erase (Dob 5220.22-M), Secure File erase, self-encryptin HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 × 660 × 1310 mm Shipping 1620 × 770 × 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 178 kg What's in the box HP DesignLet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and IOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP Smart/Stream (optional), HP SmartTracker (optional) Environmental ranges Operating humidity 20 to 80% RH Storage temperature 5 to 35%C (41 to 95%F) Operating humidity 20 to 80% RH Storage temperature -25 to 55%C (-13 to 131%F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Power Consumption <120 W (printing * scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%b), 50/60 Hz (Print languages (standard)	PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4; Non-PostScript Printer: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4
Service for Android, Apple AirPrint driver for macOS and iOS, HP Print for Chrome OS, HP Click, HP Smart App for id and Android, HP SmartSteram (optional) Drivers PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AirPrint for macOS. Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS Security features HP Secure Both, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTP Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, Ti.S. 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdwantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encryptin HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight What's in the box HP Designtet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and io/S/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (+13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Power Consumption <120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/50 Hz (±3 Hz), z. A Certification Electromagnetic Compliant with Class A requirement, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, Nevealand (RSM), China (CCC), Appantica, India); REACH; EPEAT	Print languages (optional)	Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7
PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AirPrint for macOS; Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS. Security features HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTP Secure-IPP, IPSec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encryptin HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP Designalex KJ. 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP Jetadvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating temperature -25 to 55°C (-13 to 131°F) Acoustics Sound power 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 19 dB(A) (sleep) Power Consumption <120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukrainet Singapore (PSB); China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Printing paths	Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AirPrint driver for macOS and iOS, HP Print for Chrome OS, HP Click, HP Smart App for iOS and Android. HP SmartStream (obtional)
Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encryptin HDD, encrypted PIN printing, Syslog security logging Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35%C (41 to 95%F) Operating temperature 5 to 35%C (41 to 95%F) Operating humidity 20 to 80% RH Storage temperature -25 to 55%C (-13 to 131%F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB), China (CCC), Agentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Lass A requirements, including USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (NCCI), Korea (RCC) Environmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT	Drivers	PostScript Printer: PostScript and PDF Windows drivers, raster drivers for Windows, AirPrint for macOS; Non-
Dimensions (w x d x h) Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off); Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (PCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Appan (VCCI), Korea (KCC)	Security features	JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting
Printer 1500 x 660 x 1310 mm Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating temperature 5 to 35°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Dimensions (wwd.v.h)	
Shipping 1620 x 770 x 1260 mm Weight Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating temperature 5 to 85°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		
Weight Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Citck, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)	Printer	1500 x 660 x 1310 mm
Printer Single-roll: 154 kg, dual-roll: 170 kg Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Shipping	1620 x 770 x 1260 mm
Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off). Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine I Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Weight	
Shipping Single-roll: 202 kg, dual-roll: 218 kg What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Derating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Printer	Single-roll: 154 kg, dual-roll: 170 kg
What's in the box HP DesignJet XL 3600 Multifunction Printer, printhead, introductory ink cartridges, scanner calibration sheet, 2-in right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off). Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Shipping	
right adapter kit, quick reference guide, setup poster, power cord HP Software and solutions HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantage Security Manager, HP SmartStream (optional), HP SmartTracker (optional) Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off). Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		<u> </u>
Environmental ranges Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine I Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		right adapter kit, quick reference guide, setup poster, power cord
Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		
Operating temperature 5 to 35°C (41 to 95°F) Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Environmental ranges	
Operating humidity 20 to 80% RH Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption <120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		5 to 35°C (41 to 95°F)
Storage temperature -25 to 55°C (-13 to 131°F) Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption <120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (INYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		
Acoustics Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (INYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		
Sound pressure 42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep) Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine I Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		25 (0 35 6 (-13 (0 131-1)
Sound power 5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep) Power Consumption <120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine I Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Acoustics	
Power Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine I Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Sound pressure	42 dB(A) (operating); 32 dB(A) (idle); < 19 dB(A) (sleep)
Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine V Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Sound power	5.9 B(A) (operating); 4.9 B(A) (idle); < 3.7 B(A) (sleep)
Consumption < 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off) Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine V Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT	Power	
Requirements Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		< 120 M (printing + compained): 40 M (roady): < 1.0 M (x 14 M with ambedded Distrat Front Fad) (x) 1.0.2 M (x 15 M)
Certification Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM, New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		
Safety USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; ROHS (EU, China, Korea, India); REACH; EPEAT		input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A
Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACM/New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT	Certification	
New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC) Environmental ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT	Safety	USA and Canada (CSA certified); EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA) Singapore (PSB); China (CCC); Argentina (IRAM); Mexico (NYCE); India (BIS)
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC)
Warranty 90-day limited hardware warranty	Environmental	ENERGY STAR; WEEE; RoHS (EU, China, Korea, India); REACH; EPEAT
30 day minica naranare mananary	Warranty	90-day limited hardware warranty

Ordering information

HP DesignJet XL 3600 36-in Multifunction Printer
HP DesignJet XL 3600 36-in Multifunction Printer with PostScript/PDF
HP DesignJet XL 3600d 36-in Multifunction Printer
HP DesignJet XL 3600d 36-in Multifunction Printer with PostScript/PDF 6KD23A 6KD24A

Accessories

2NH46AAF 2NH47AAE

3JJ54A HP SmartTracker LISB for HP XL 3000 Printer series HP SmartTracker USB for HP XL 3000 Printer series
HP SmartTracker HP XL 3000 Printer series
HP DesignJet XL 3600 MFP Folder Upgrade Kit
HP SmartStream Print Controller USB for HP XL 3000 Printer series
HP SmartStream Print Controller for HP XL 3000 Printer series
HP DesignJet PostScript/PDF Upgrade Kit
HP SmartStream USB Preflight Manager
HP SmartStream Preflight Manager
HP SmartStream Document Organiser Module
HP SmartStream Pixel Analysis Module 6CC86AAE 6SE87A 6SE88A 6SE88AAE C0C66C L3J69A L3J69AAE

Original HP printing supplies

HP 727\732 Designjet Printhead HP 765 300ml (yan Design)let Inlinded HP 766 300ml (yan Design)let Ink Cartridge HP 766 300ml Magenta Design)let Ink Cartridge HP 7668 300ml Potto Black Design)let Ink Cartridge HP 766B 300ml Broto Black Design)let Ink Cartridge HP 766B 300ml Matte Black Design)let Ink Cartridge P2V90A P2V91A 3FD55A

Use Original HP inks and printheads, and HP large format printing materials, to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimised printing system, and Original HP inks are designed to maximise the life of HP printheads. Protect your HP printer investment by using Original HP inks for full HP warranty protection. For more information, visit hp.com/go/OriginalHPinks.

Original HP large format printing materials

C6810A HP Bright White Inkjet Paper (FSC® certified)⁵ (recyclable)⁶ 914 mm x 91.4 m (36 in x 300 ft)

C6980A HP Coated Paper (PEFC™ certified)⁵ (recyclable)⁶ 914 mm x 91.4 m (36 in x

LSC80A HP Universal Heavyweight Coated Paper, 3-in Core (FSC® certified)⁵ (recyclable)⁶ 914 mm x 91.4 m (36 in x 300 ft)

D9R28A HP Everyday Matte Polypropylene, 3-in Core 914 mm x 61 m (36 in x 200 ft)

Service and Support

UCGG7E HP 3-year NBD HW Support with DMR
UCGG8E HP 4-year NBD HW Support with DMR
UCGG8E HP 5-year NBD HW Support with DMR
UCGG9E HP 5-year NBD HW Support with DMR
UCGH0PE HP 1-year Post Warranty NBD HW Support with DMR
UCGH1PE HP 2-year Post Warranty NBD HW Support with DMR
UCGH1PE HP 1-year Post Warranty NBD HW Support with DMR
UCGH1PE HP 1-year Post Warranty NBD HW Support with DMR
UCGH1PE HP 1-year Post Warranty NBD HW Support with DMR

HP DesignJet Support Services offer installation, maintenance, and extended suppor services (e.g. 2,3, 4 and 5 years). For more information, please visit hp.com/go/cpc

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

ECO highlights

- Save paper with automatic print settings and image nesting ENERGY STAR® certified *and EPEAT® registered *Free, convenient HP ink cartridge recycling *FSC®-certified papers *4, recyclable HP media; some HP media eligible for takeback program *5.

Please recycle large-format printing hardware and printing supplies. Find out how at $\,$

1 ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.
2 EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
3 Program availability varies. Please check http://www.hp.com/recycle for details.
4 BMG trademark license code FSC®-C115319, see http://www.fsc.org, HP trademar license code FSC®-C017543, see http://www.fsc.org. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials' please visit http://www.HPLFMedia.com/.
3 Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ccosolutions for details.

exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Brigh^t White Inkjet Paper (bond) and Original HP inks.

² ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original HP inks.

³ Measured on HP Matte Film.

⁴ Based on § CR PAM.

4 Based on 8 GB RAM.

⁴ Based on 8 GB RAM.

S BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. BMG trademark license code FEFC™/29-31-261, see http://www.pefc.org. HP trademark license code PEFC™/29-31-261, see http://www.pefc.org. HP trademark license code PEFC™/29 31-198, see http://www.pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.

6 Can be recycled through commonly available recycling programs.

7 Applicable for dual-roll printers only.

Applicable for dual-roll printers only













