# HP Latex 800 W Printer



## Win high-value jobs with white ink and productive printing—and sharpen your sustainability edge



## Expand into white, produce the highest value jobs

- Extend your portfolio into high-margin stickers and window graphics with the whitest white
- Print white without complexity—automatic recirculation and printhead cleaning reduce manual purging.
- Deliver vivid colours at high speed, get striking contrast using pure blacks, and expect sharp 4-point text.
- Choose from a wide application range covering banners/textiles/poster paper, canvas, wallpaper, and vinyl.

## Robust, smart, and productive printing

- Drive high productivity with saturated colour at speeds up to 36 m<sup>2</sup>/hr outdoor<sup>2</sup>, easy spindle-less loading.
- Control print operations virtually anytime, anywhere with HP PrintOS tools, and grow with HP Learn trainings.
- Work fast processing reprints and multi-copy jobs with a smart front panel, and store up to 100 jobs.
- Help reduce running costs with cost-effective 3-liter HP ink cartridges, changed while the printer runs.

## Sharpen your sustainability edge with HP Latex

- Innovative water-based HP Latex Inks-no HAPs<sup>3</sup>, no required hazard warning labels, and odorless prints.4
- Local HP Eco-Carton outer carton recycling.5
- Choose from a wide range of compatible ecoconscious media.6
- HP Latex prints are recyclable, returnable, or non-hazardous and safe for disposal.7

## For more information, please visit http://www.hp.com/go/latex800series

### Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

<sup>1</sup> Whitest white based on ISO/DIS 23498 compared to competitive alternatives using solvent and UV technologies under \$50,000 USD as of May, 2020. Test performed on black opaque self-adhesive vinyl (1.\*.4.16 –

a:0,48-b:2,34) with 160% UF printmode using HP 873 3-liter White Latex Ink Cartridge. Visual opacity = 91%.

Outdoor mode (Banner) 4-pass, 100%. Based on internal HP testing in September 2020 on Avery 3001. Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

HP Latex Inks were tested for Hazardous Air Pollutants, as defined in the Clean Air Act, per U.S. Environmental Protection Agency Method 311 (testing conducted in 2013) and none were detected.

<sup>&</sup>lt;sup>4</sup> There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. <sup>5</sup> The ink cartridge outer carton is 100% recyclable through local cardboard/paper programs.

<sup>6</sup> See http://www.hp.com/go/mediasolutionslocator
7 Most HP large format paper-based printing materials can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the free, convenient HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details. HP large format printing materials, both unprinted and printed with Original HP Latex Inks, are non-hazardous and safe for disposal. Contact your local waste management authority for local area-specific instructions.

## Technical specifications

| Print                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing modes                            | 122 m²/hr - MaxSpeed (1-pass) 36 m²/hr - High Speed (4-pass) 25 m²/hr - Production Fast (6-pass) 20 m²/hr - Production Quality, Textites and Backlits (8-pass) 21 m²/hr - Production Quality, Textites and Backlits (8-pass) 11 m²/hr - High Saturation (12-pass) 14 m²/hr - High Saturation Backlits and Textiles (14-pass) 17 m²/hr - White Spot (60%) 9 m²/hr - White Underflood (100%) 3 m²/hr - White Underflood (100%) 2 m²/hr - Jayers Day & Nghrift (160%) 1 m²/hr - White Underflood (100%) |
| Print resolution                          | Up to 1200 x1200 dpi                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Inktypes                                  | Water-based HP Latex Inks                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Inkcartridges                             | 9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)                                                                                                                                                                                                                                                                                                                                                                                            |
| Cartridgesize                             | 3 L                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Printheads                                | 10 (2 cyan/black, 2 magenta/yellow, 2 light cyan/light magenta, 2 white, 1 HP Latex Optimizer, 1 HP Latex Overcoat)                                                                                                                                                                                                                                                                                                                                                                                  |
| Long-term print-to-print<br>repeatability | 95% of colours ≤ 1.5 dE2000 <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Media                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Handling                                  | Roll feed, take-up reel, wiper roller <sup>3</sup> , media saver, automatic horizontal cutter (for vinyl, banner and canvas <sup>4</sup> , paper-based media, and film)                                                                                                                                                                                                                                                                                                                              |
| Mediatypes                                | Banners, self-adhesive vinyls, films, fabrics, papers, wall coverings, canvas, synthetics, mesh, textiles <sup>5</sup>                                                                                                                                                                                                                                                                                                                                                                               |
| Rollsize                                  | 419 to 1625-mm rolls (580 to 1625-mm rolls with full support)                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Roll weight                               | 55 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Roll diameter                             | 250 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Thickness                                 | Up to 0.5 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Applications                              | Banners; Displays; Exhibition and event graphics; Exterior signage: Indoor posters; Interior decoration; Light boxes - Film; Light boxes - paper; Murals; POP/POS; Posters; Textile; Vehicle graphics; Window graphics; Stickers                                                                                                                                                                                                                                                                     |
| Connectivity                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Interfaces                                | Gigabit Ethernet (1000Base-T)                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Dimensions (W x D                         | xH)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Printer                                   | 2583 x866 x1402 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Shipping                                  | 2753×1100×1666 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Operating area                            | 2793 x2100 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Weight                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Printer                                   | 300 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Shipping                                  | 443 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| What's in the box                         | HP Latex 800 W Printer, printheads, maintenancecartridge, printer stand, take-up red, media loading accessory, user maintenancekit, degeholders, quick referenceguide, documentation software, power cords, air purges, 2-in spindle adaptor                                                                                                                                                                                                                                                         |
| Environmental rang                        | ges                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Operating temperature                     | 15 to 30°C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Operating humidity                        | 20 to 80% RH (non-condensing)                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Acoustics                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Sound pressure                            | 60 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Sound power                               | 7.8 B(A) (operating), 5.5 B(A) (idle), <3.5 B(A) (sleep)                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Power                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Consumption                               | 1.8-2.8 kW (5 kW peak) (printing), 105 W (ready)                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Requirements                              | input voltage (autoranging) 200-240 V ( $\pm 10\%$ ) two wires and PE; 50/60 Hz ( $\pm 3$ Hz); two power cords; 16 A max per power cord                                                                                                                                                                                                                                                                                                                                                              |
| Certification                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Safety                                    | IEC 60950-1+A1+A2 compliant; IEC 62368-1 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN62368-1 compliant); Russia, Belarus, and Kazakhstan (EAC); China (CCC)                                                                                                                                                                                                                                                                                                                    |
| Electromagnetic                           | Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)                                                                                                                                                                                                                                                                                                                          |
|                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Environmental                             | ENERGY STAR®, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT Silver, OSHA;<br>CE marking compliant; Meets AgBB criteria; French VOC A+; Greenguard Gold; UL Ecologo; ZDHC – Level 1                                                                                                                                                                                                                                                                                       |

## Ordering information

## Product

| 3XD61A      | HP Latex 800 W Printer                    |  |
|-------------|-------------------------------------------|--|
| Accessories |                                           |  |
| 21V10A      | HP Latex 700/800 User Maintenance Kit     |  |
| 42153A      | HP Latex Media Feed Accessory             |  |
| 7HR16A      | HP Latex 700/800 Textile Kit Accessory    |  |
| 7HR18A      | HP Latex 700/800 Ink Collector Foam's Kit |  |
| 7HR19A      | HP Latex 700/800 Media Loading Accessory  |  |
| T7U73A      | HP Latex 500/700/800 Wiper Roller         |  |

| 4UU93A | HP 836 White Latex Printhead                     |  |
|--------|--------------------------------------------------|--|
| 4UU94A | HP 836 Optimizer Latex Printhead                 |  |
| 4UU96A | HP 836 Latex Maintenance Cartridge               |  |
| 4UV62A | HP 873 3-liter White Latex Ink Cartridge         |  |
| 4UV84A | HP 873 3-liter Black Latex Ink Cartridge         |  |
| 4UV85A | HP 873 3-liter Cyan Latex Ink Cartridge          |  |
| 4UV86A | HP 873 3-liter Magenta Latex Ink Cartridge       |  |
| 4UV87A | HP 873 3-liter Yellow Latex Ink Cartridge        |  |
| 4UV88A | HP 873 3-liter Light Cyan Latex Ink Cartridge    |  |
| 4UV89A | HP 873 3-liter Light Magenta Latex ink Cartridge |  |
| 4UV90A | HP 873 3-liter Optimizer Latex Ink Cartridge     |  |
| 4UV91A | HP 873 3-liter Overcoat Latex Ink Cartridge      |  |
| 4UV95A | HP 836 Black/Cvan Latex Printhead                |  |
| 4UV96A | HP 836 Magenta/Yellow Latex Printhead            |  |
| 4UV97A | HP 836 Light Cyan/Light Magenta Latex Printhead  |  |
| 4UV98A | HP 836 Overcoat Latex Printhead                  |  |
|        |                                                  |  |

### Original HP large format printing materials

- HP PVC-free Wallpaper (UL GREENGUARD GOLD Certified<sup>6</sup>, FSC® certified<sup>7</sup>, meets Ag BB criteria<sup>9</sup>) HP Photo-reelistic Poster Paper HP Premium Satin Canvas HP Prime Matte Air GP (REACH compliant<sup>9</sup>) HP Premium Removable Gloss Adhesive Vinyl (REACH compliant<sup>9</sup>)

 $For the \,entire \,HP \,Large \,Format \,Printing \,Materials \,portfolio, \,please \,see \,HPLFMedia.com.$ 

### Service and Support

U13DDE HP 2 year Next Business Day with Defective Media Retention
U13DJE HP 3 year Next Business Day with Defective Media Retention
U13DNFE HP 1 year Post Warranty Next Business Day with Defective Media Retention
U13DTPE HP 2 year Post Warranty Next Business Day with Defective Media Retention

## ECO highlights

- Inks do not use reactive monomer chemistry, are ozone-free, and meet the ZDHC standard  $^1$  Can win new business with odour tesp prints, ULECOLOGO®/ULGREENGUARD Gold Certified ink, and more High-volume 3-litter HP Eco-Carton ink cartidges—carton-based design significantly reduces plastic

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

<sup>1</sup> Seehttp://www.roadmaptozero.com . Printing with HP Latex hks avoids the problematic reactive monomers associated with UV printing. Acrylate monomers present in uncured UV inks and UV-gel inks can damage skin. <sup>2</sup> There is a broad set of media with very different odour profiles. Some of the media can affect the odour performance of the final print. For certifications, see http://www.ul.com/EL and http://www.ul.com/gg

Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects.

The colour variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 colour target under CE standard Illumin ant DSO, and according to the standard CEDE 2000 as per CE Draft standard DSI -5% of colours may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results.

"Wiper roller is an optional accessory."

Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.

Textle kit Accessory required for long runs of textle and porous textile.

"ULGREENGUARD GOLD Certification to UL2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit bits://www.ul.com/gg.orhtp://www.greenguard.org/
Trademark license code FSC-C-115319.

With HP Latex hks, prints meet Ag BB criteria for health-related evaluation of VOC emissions. See http://unwelbundesamt.de/en/topics/health/related-evaluation-of-building
This product does not contain substances listed as SVHC (155) per Annex XV of the EUREACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at HP Printing Products and Consumable Supplies.



















