

imagePROGRAF
PRO-6100

REALISE STUNNING PRINT QUALITY WITH ADVANCED SECURITY

A large format solution for
print service providers in the
photographic and fine art markets.



- **Save ink costs**

Remaining media estimation prevents wasted ink by telling you exactly how much media you have left

- **Secure printing**

Restrict print connections and access by setting user security levels and individual passcodes

- **Smart software**

Intuitively control pre-print settings on-screen for precision output, with Professional Print

- **All media types/Auto media type detection**

A sensor detects the media, matches it with an internal database and automatically selects the media type

- **Borderless print**

Print various-sized borderless images from one roll size, with high margin adjustment accuracy

PRODUCT RANGE



imagePROGRAF PRO-2100



imagePROGRAF PRO-4100



imagePROGRAF PRO-6100

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF PRO-6100

TECHNOLOGY

| | |
|---------------------|--|
| Printer Type | 12 Colour 60"/1524mm |
| Print Technology | Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head) |
| Print Resolution | 2,400 x 1200 dpi |
| Number of Nozzles | 18,432 nozzles (1536 nozzles x 12 colour) |
| Line Accuracy | 30.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only |
| Nozzle Pitch | 600 dpi x 2 includes Non-firing nozzle detection and compensation system |
| Ink Droplet Size | minimum 4 pl per colour |
| Ink Capacity | Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 330ml |
| Ink Type | Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser |
| OS Compatibility | Microsoft Windows: 32 Bit, Vista, 7, 8, 8.1, 10 Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2, Windows Server 2019 Apple Macintosh: OS X 10.11.6, macOS 10.12-macOS 10.15 |
| Printer Languages | SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02) |
| Standard Interfaces | USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN |

MEMORY

| | |
|-----------------|-----------------------|
| Standard memory | 3 GB |
| Hard Drive | 500GB (Encrypted HDD) |

PRINT TIME FOR A0 PAGE SIZE

| | | |
|--------------------|------------------------|------------|
| Media Type | Print Mode: Print Time | |
| Plain Paper | Print Mode | Print Time |
| | Fast | 1:37 min |
| Coated Paper | Standard | 2:49 min |
| | Print Mode | Print Time |
| | Standard | 2:49 min |
| Glossy Photo Paper | High Quality | 5:35 min |
| | Print Mode | Print Time |
| | Standard | 5:35 min |
| | High Quality | 8:50 min |

MEDIA HANDLING

| | |
|-----------------------------|--|
| Media Feed and Output | Upper Roll Paper: One Roll, Front-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever) |
| Media Width | Roll paper: 152.4 -1524 mm Cut sheet: 152.4 - 1524 mm |
| Media Thickness | Roll/Cut: 0.07 - 0.8 mm |
| Minimum Printable Length | 203.2 mm |
| Maximum Printable Length | Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m |
| Maximum Media Roll Diameter | 170 mm |
| Media Core Size | Internal diameter of roll core: 2"/3" |
| Margins Recommended area | Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm |
| Margins Printable area | Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm |

Media Feed Capacity

Media Take-up roll unit

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)

Packaged Dimensions WxDxH (mm) and Weight (Kg)

POWER AND OPERATING REQUIREMENTS

Power Supply

Power Consumption

Operating Environment

Acoustic Noise (Power/Pressure)

Regulations

Certificates

WHAT'S INCLUDED

What's in the Box?

Software Included

OPTIONS

Optional Items

CONSUMABLES

User Replaceable Items

Roll Paper: Two rolls. Automatic switching is possible.
Cut Sheet: 1 sheet

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

515mm(JIS B2), 728mm(JIS B1), 1030mm(JIS B0),
594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36",
42", 44", 50", 54", 60", 257mm(JIS B4)*, 297mm(ISO A3)*, 329mm(ISO A3+)*, 420mm(ISO A2)*, 6", 8", 12",
16", 20", 22", 30", 300mm*, 500mm, 600mm 800mm,
1000mm and custom roll width (152.4-1524mm)

*Some environmental conditions may not produce the desired result

Standard position: 1 sheet

Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

1999 x 984 x 1168 mm (Basket Open)

1999 x 766 x 1168 mm (Basket Closed)

171kg (including Roll Holder Set and Roll unit, excluding ink and print heads)

Printer (Main unit with pallet): 2227 x 915 x 1022 mm

212kg

Roll Unit: 2133 x 562 x 461 mm

42kg

AC 100-240V (50-60Hz)

Operation: 97 W or less

Sleep mode: 2.1W or less

Default setting for the time to enter the Sleep mode:

Approx. 5 Minutes

Power off: 0.3 W or less

Temperature: 15-30°C,

Humidity: 10-80% RH (no dew condensation)

Operation: approx. 48 dB (A)

(Glossy paper, Print priority: Standard)

Standby: 35 dB (A) or less

Operation: 6.6 Bels or less

(Glossy paper, Image, Print priority: Standard)

(Measured on ISO 7779 standard)

Europe: CE mark, Russia: EAC

TUV, CB

Printer, 1print heads, 3 inch paper core attachment,
Power Cable, 1 set of starter ink tanks, Set up guide,
Safety/Standard Environment leaflet, User software
CD-ROM (Win), PosterArtist Lite CD-ROM,
EU Biocide Sheet, Eurasian Economic Union Sheet,
Important Information Sheet

imagePROGRAF PRO Printer Driver

Other software available as Download from Web.

2/3" Roll Holder: RH2-66

Roll Unit: RU-63

Ink Tank: PFI-1100 (160ml), PFI-1300 (330ml),
PFI-1700 (700ml)
Print Head: PF-10
Cutter Blade: CT-07
Maintenance Cartridge: MC-30

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice." and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



STANFORD MARSH
STANFORD MARSH GROUP

www.stanfordmarsh.co.uk
info@stanfordmarsh.co.uk | 0844 856 0701

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2019

