
RICOH imagine, change. **Colour Multifunction Printer MP C2004ex** MP C2504ex **MP C3004ex MP C3504ex** MP C4504ex MP C5504ex **MP C6004ex Series** ☑ Copier ☑ Printer ☑ Facsimile ☑ Scanner MP C3504ex MP 2004ex MP C2504ex MP C3004ex 30 Colour 35 Colour 45 Colou 55 Colour 60 Colour

Much more than a new range. It is a whole new way to connect your business.

With thirteen models available, these hard workers form part of our flagship A3 colour Smart MFP range. Each model offers superb reliability, output quality and workplace productivity – so no matter which one you choose, these are the perfect devices for your high output, multipurpose environment. These devices have a Smart Operation Panel and they are designed to help you increase productivity thanks to their rich functionality – including several finishing options, banner printing capabilities and a new Intel processor.





MP C2004ex/MP C2504ex/MP C3004ex/MP C3504ex/MP C4504ex/MP C5504ex/MP C6004ex/Series

MAIN SPECIFICATIONS

GENERAL

Warm-up time: 25/25/25/25/24/24/24 seconds First output speed: Full colour: 7.6/7.5/7.1/7.1/5.7/4.5/4.5

seconds

B/W: 5.4/5.3/4.6/4.6/4/3.1/3.1 seconds 20/25/30/35/45/55/60 pages per minute

Continuous output speed Maximum: 4 GB Memory

250/250/250/250/320/320/320 GB HDD:

Dimensions (W x D x H): 587 x 685 x 913 mm

With SPDF: 587 x 685 x 963 mm

Weight: With ARDF: 91.5/91.5/95.6/95.6/

97.7/97.7 kg

With SPDF: 97.2/97.2/101.3/101.3/ 103.4/103.4/103.4 kg

220 - 240 V, 50/60 Hz Power source

COPIER

Multiple copying: Up to 999 copies 600 dpi/4 bit Resolution:

From 25% to 400% in 1% steps Zoom:

PRINTER

Printer language: Standard: PCL5c, PCL6(XL),

PostScript 3 (emulation), PDF direct

(emulation)

Option: Genuine Adobe ®PostScript®3™, XPS, IPDS, PictBridge, PDF Direct from Adobe®

Print resolution: Maximum: 1.200 x 1.200 dpi Interface:

Standard: USB Host I/F. Ethernet 10 base-T/100 base-TX/1000 base-T

Option: USB 2.0. Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, Additional NIC (2nd port), Bi-directional IEEE

1284/ECP

Windows® 7. Windows® 8.1. Windows® environments:

Windows® 10, Windows® Server 2008. Windows® Server 2008R2. Windows® Server 2012, Windows®

Server 2016

Mac OS environments: Macintosh OS X v10.9 or later UNIX environments:

UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux Enterprise, IBM® AIX, IBM® System

i5™ HPT, XenDesktop

SCANNER

Scanning speed: ARDF: Max. 80 originals per minute SPDF: Max. 110 (simplex)/180

(duplex) originals per minute

Maximum: 1,200 dpi (Twain) Resolution: Original size A3, A4, A5, B4, B5, B6 Bundled drivers: Network TWAIN E-mail, SMB, FTP, URL Scan to:

FAX

Circuit: PSTN. PBX Compatibility: ITU-T (CCITT) G3

Resolution: Standard: 8 x 3.85 line/mm, 200 x 100

dpi, 8 x 7.7 line/mm, 200 x 200 dpi Option: 8 x 15.4 line/mm, 400 x 400 dpi, 16 x 15.4 line/mm, 400 x 400 dpi G3: 2 second(s) (200 x 100 dpi, JBIG),

3 second(s) (200 x 100 dpi, MMR)

Maximum: 33.6 Kbps Modem speed:

PAPER HANDLING

Transmission speed

Paper input capacity: Maximum: 2,300/2,300/4,700/4,700/

4,700/4,700/4,700 sheets

Maximum: 1.625/1.625/1.625/1.625/ Paper output capacity 3.625/3.625/3.625 sheets

Paper weight: 52 - 300 g/m²

- g/m²

ECOLOGY

Power consumption: Maximum: 1,700/1,700/1,700/1,700/

1.850/1.850/1.850 W

Ready mode: 50.2/50.2/47.3/47.3/55.1/ 55.1/55.1 W

Sleep mode: 0.9/0.9/0.93/0.93/0.89/

0.89/0.89 W

TEC (Typical Electricity Consumption): 0.7/0.9/1.2/1.3/1.8/2.5/2.7 kWh

OPTIONS

ADF handle, 1 x 550-sheet paper tray, 2 x 550-sheet paper tray, 2,000sheet large capacity tray, 1,500-sheet side large capacity tray, Bridge unit, 1.000-sheet Hybrid finisher, 3.000-sheet finisher, Internal finisher, Internal finisher with stapleless stapler, 1,000-sheet booklet finisher, 2,000-sheet booklet finisher, Punch kits, Internal shift tray, One-bin tray, Side tray, Caster table, Cabinet, Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), Bluetooth, Pictbridge, Genuine Adobe ®PostScript®3™, IPDS unit, Counter interface, File format converter, Key counter bracket, Card reader bracket, Data Overwrite Security Unit (Certified version), Fax Connection Unit, Fax marker, 2nd Super G3 port, Fax memory, Fax option, Unicode Font Package for SAP, OCR Unit, Smart Card Reader Built-in Unit, SRA3 unit, XPS direct print, Enhanced security HDD, External keyboard bracket, NFC Card Reader, Banner paper tray guide, G3 Interface unit, EFI colour controller, Extended USB board, 4GB Memory

CONSUMABLES

Toner capacity: Black: 15,000/15,000/29,500/29,500/

33,000/33,000/33,000 prints Cyan/Magenta/Yellow: 9,500/9,500/ 18,000/18,000/22,500/22,500/22,500 prints

Consumable yield figures are based on

2 p, i 5% coverage on A4

For availability of models, options and software, please consult your local supplier

ISO9001 certified ISO14001 certified. ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2018 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

RICOH imagine, change.

www.ricoh-europe.com

