

Work smarter and more effectively with the IM C4500LT/5500ALT/6000LT intelligent devices – new technology that is designed to grow and adapt, just as your business does.

### It's time to:

- Work smarter using integrated workflow scan processes
- Get personal with easy access to the apps you use most often
- Stay current add new functions as needed
- Save costs by reduced energy consumption


Have access to essential feature enhancements and upgrades, whenever you need them. Boost productivity by seamlessly integrating apps from our secure application site to optimise and streamline your workflow. Have confidence that your intelligent devices are ready to meet all your demands now and in the future – using technology that's scalable, secure, sustainable and simple.

## Get more from your intelligent device:

- Save time and streamline workflow with the right finishing solution for the job
- Scan smaller documents with the small size paper scan
  unit
- Improved scan accuracy double feed detection unit
- Enhance print management with EFI controller

Take advantage of a variety of finishing and paper options to add a professional touch whilst meet-ing the printing demands of medium to large workgroups. Environmentallyfriendly low TEC (Typical Electricity Consumption) values, deliver reduced energy consumption and cut running costs. RICOH Intelligent Support tools ensure your device uptime is maximised whilst self-help tools enable your teams to make simple fixes such as changing supplies, without involving expensive IT-resources. With print speeds from 45 to 60 CPM, the IM C4500LT/ 5500ALT/6000LT devices are here to add value to your business. The easy-to-use 10.1" Smart Operation Panel with touch screen controls has improved responsiveness and large new look icons. Settings can be configured to suit each individual user's needs and with easier mobile connectivity, users can print or scan to the office network or cloud from their smart device, with built-in support for NFC, AirPrint\* or Mopria.

- Production of professional flyers with inner multi-folding unit
- Reduction of outsourcing costs by producing printed materials in-house
- Efficient working and reduced user intervention by expanding paper capacity
- Increased uptime and performance with RICOH
   Intelligent Support



# IM C4500LT/IM C5500ALT/IM C6000LT hardware configuration

# RICOH IM C4500LT/ IM C5500ALT/ IM C6000LT

MAIN SPECIFICATIONS

ENERAL	IM C4500LT	Г	IM C5500ALT	IM	I C6000LT
Varm-up time			21 seconds		
irst output speed: B/W	4 seconds		3.1 seconds	3	.1 seconds
irst output speed: full colour	5.7 seconds		4.6 seconds		.6 seconds
ontinuous output speed	45 ppm		55 ppm	-	60 ppm
emory: standard	40 ppm		2 GB		oo ppin
•			4 GB		
emory: maximum					
DD: standard			320 GB		
DD: maximum			320 GB		
RDF capacity (IM C4500LT )	100 sheets		-		-
PDF capacity (IM C5500ALT,	-		220 sheets	2	20 sheets
1 C6000LT)					
/eight	96 kg		101.4 kg		101.4 kg
imensions: W x D x H	587 x 685 x 913 n	nm	587 x 685 x 963 mm	587 x	685 x 963 mm
ower source	220 - 240 V, 50 - 6	0 Hz	220 - 240 V, 50 - 60 Hz	220 - 2	40 V, 50 - 60 Hz
OPIER					
ultiple copying			Up to 999 copies		
esolution	600 dpi		600 dpi		600 dpi
moc		Fr	rom 25% to 400% in 1% step	DS	
RINTER					
			Apollolake A3950 1.6 GHz		
rinter language: standard			•	direct (emulation)	
• •	-		stScript 3 (emulation), PDF		
rinter language: option	G	enuine Adobe® PostSc	rript®3™, IPDS, PictBridge, I	PDF Direct from Adobe®	
rint resolution: maximum			1,200 x 1,200 dpi		
etwork interface: standard	Ethernet	10 base-T/100 base-TX	//1000 base-T, USB Host I/F	Type A, USB Device I/F	Туре В
etwork interface: option			eless LAN (IEEE 802.11a/b/		
obile printing capability			nt, NFC, Ricoh Smart Device		· ·
indows® environments	Mindowe® 7 Mindowe®				dower Server 2012
	vviiliuuws⊚7, vviiliuuWS®		dows® Server 2008, Windo Server 2016, Windows® Se		
ac OS environments		Macin	ntosh OS X Native v10.11 or	later	
NIX environments	UNIX	Sun® Solaris, HP-UX,	SCO OpenServer, RedHat®	Linux Enterprise, IBM®	AIX
AP® environments			SAP® R/3®, SAP® S/4®		
Other supported environments			IBM iSeries		
CANTER		200 dai)			
conning anode ADDE (IM	00 inm (200				
• • •	80 ipm (200	300 dpi)	-	-	
4500LT)	80 ipm (200 -		- 240 ipm (duplex)	- 120 ipm (simplex)	240 ipm (duplex)
4500LT ) canning speed: SPDF (IM	80 ipm (200 -	120 ipm (simplex)	- 240 ipm (duplex)	- 120 ipm (simplex)	240 ipm (duplex)
4500LT ) canning speed: SPDF (IM 5500ALT, IM C6000LT)	80 ipm (200 -		- 240 ipm (duplex)	- 120 ipm (simplex)	240 ipm (duplex)
icanning speed: ARDF (IM 24500LT ) icanning speed: SPDF (IM 25500ALT, IM C6000LT) Resolution: maximum iile formats	80 ipm (200 - Single Page TIFF, Single p Single page PDF/A, Mul	120 ipm (simplex) 1,200 dpi page JPEG, Single page	High compression PDF,	- 120 ipm (simplex)	240 ipm (duplex)
4500LT) canning speed: SPDF (IM :5500ALT, IM C6000LT) esolution: maximum	- Single Page TIFF, Single p Single page PDF/A, Mul	120 ipm (simplex) 1,200 dpi page JPEG, Single page	High compression PDF, PDF, Multi page High	- 120 ipm (simplex)	240 ipm (duplex)
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats	Single Page TIFF, Single p Single page PDF/A, Mul compre	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page Ission PDF, Multi page F	e High compression PDF, e PDF, Multi page High PDF/A	- 120 ipm (simplex)	240 ipm (duplex)
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes	Single Page TIFF, Single p Single page PDF/A, Mul compre	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page	e High compression PDF, e PDF, Multi page High PDF/A	- 120 ipm (simplex)	240 ipm (duplex)
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum lie formats can modes	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page Ission PDF, Multi page F	e High compression PDF, PDF, Multi page High PDF/A RL, FTP		
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit	Single Page TIFF, Single p Single page PDF/A, Mul compre	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page Ission PDF, Multi page F	e High compression PDF, PDF, Multi page High PDF/A RL, FTP PSTN, PBX		240 ipm (duplex) 'STN, PBX
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page Ission PDF, Multi page F	e High compression PDF, e PDF, Multi page High DDF/A RL, FTP PSTN, PBX 2 seconds		
4500LT) aanning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum e formats aan modes ax rcuit ansmission speed	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page Ission PDF, Multi page F	e High compression PDF, PDF, Multi page High PDF/A RL, FTP PSTN, PBX		
4500LT) aanning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum e formats an modes ax rcuit ansmission speed odem speed: maximum	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page ession PDF, Multi page F older, USB, SD Card, Ul	e High compression PDF, e PDF, Multi page High DDF/A RL, FTP PSTN, PBX 2 seconds	F	
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed odem speed: maximum esolution: standard	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page sision PDF, Multi page f bilder, USB, SD Card, Ul	P High compression PDF, PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps	F	
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed odem speed: maximum esolution: standard esolution: option	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page sision PDF, Multi page f bider, USB, SD Card, Ul	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp	F	
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX ircuit ransmission speed odem speed: maximum esolution: standard esolution: option pompression method	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page sision PDF, Multi page f bider, USB, SD Card, Ul	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG	F	'STN, PBX
4500LT) canning speed: SPDF (IM 5500ALT, IM C600LT) esolution: maximum le formats can modes AX rcuit ansmission speed odem speed: maximum esolution: standard esolution: option pmpression method canning speed	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page sision PDF, Multi page f bider, USB, SD Card, Ul	PDF, Multi page High PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 33.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm	F	
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed odem speed: maximum esolution: standard esolution: option ompression method canning speed emory: standard	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page sision PDF, Multi page f bider, USB, SD Card, Ul	PBF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 33.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages)	F	'STN, PBX
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed odem speed: maximum esolution: standard esolution: option ompression method canning speed emory: standard	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page sision PDF, Multi page f bider, USB, SD Card, Ul	PDF, Multi page High PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 33.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm	F	'STN, PBX
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX ircuit ransmission speed odem speed: maximum esolution: standard esolution: option ompression method canning speed emory: standard emory: maximum	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi bage JPEG, Single page Iti page TIFF, Multi page sision PDF, Multi page f bider, USB, SD Card, Ul	PBF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 33.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages)	F	'STN, PBX
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page Iti page TIFF, Multi page F sission PDF, Multi page F older, USB, SD Card, UI 1 Standard paper tray(s	e High compression PDF, e PDF, Multi page High DDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages)	P 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	'STN, PBX
4500LT) anning speed: SPDF (IM 5500ALT, IM C6000LT) asolution: maximum le formats an modes AX rcuit ansmission speed odem speed: maximum asolution: standard asolution: option ompression method canning speed emory: standard emory: standard emory: maximum APER HANDLING	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page Itir page TIFF, Multi page ission PDF, Multi page f plder, USB, SD Card, UI 1 Standard paper tray(s Optional paper tray(s	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages)	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes	°STN, PBX 81 spm
4500LT) anning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum e formats an modes AX rcuit ansmission speed bodem speed: maximum esolution: standard esolution: option solution: option solution: option mpression method canning speed emory: standard emory: standard emory: maximum APER HANDLING	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page Itir page TIFF, Multi page ission PDF, Multi page f plder, USB, SD Card, UI 1 Standard paper tray(s Optional paper tray(s	e High compression PDF, e PDF, Multi page High DDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages)	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes	°STN, PBX 81 spm
4500LT) canning speed: SPDF (IM 5500ALT, IM C600LT) esolution: maximum le formats can modes AX rcuit ansmission speed odem speed: maximum esolution: standard esolution: option pompression method canning speed emory: standard emory: standard emory: maximum APER HANDLING ecommended paper size	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page Itir page TIFF, Multi page ission PDF, Multi page f plder, USB, SD Card, UI 1 Standard paper tray(s Optional paper tray(s	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages)	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes	°STN, PBX 81 spm
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed odem speed: maximum esolution: standard esolution: option pompression method canning speed emory: standard emory: maximum APER HANDLING ecommended paper size aper input: standard	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page Itir page TIFF, Multi page ission PDF, Multi page f plder, USB, SD Card, UI 1 Standard paper tray(s Optional paper tray(s	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages) s): SRA3, A3, A4, A5, A6, B4 (4, A5, A6, B4, B5, B6, Enve 1,200 sheets	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes	°STN, PBX 81 spm
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rouit ansmission speed odem speed: maximum esolution: standard esolution: option pompression method canning speed emory: standard emory: standard emory: maximum APER HANDLING ecommended paper size aper input: standard aper input: maximum	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page Itir page TIFF, Multi page ission PDF, Multi page f plder, USB, SD Card, UI 1 Standard paper tray(s Optional paper tray(s	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages) 5): SRA3, A3, A4, A5, A6, B4 (4, A5, A6, B4, B5, B6, Enve 1,200 sheets 4,700 sheets	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes	°STN, PBX 81 spm
4500LT) anning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed oddem speed: maximum esolution: standard esolution: option pmpression method canning speed emory: standard emory: standard emory: maximum APER HANDLING ecommended paper size aper input: standard aper input: standard aper output: standard	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page Itir page TIFF, Multi page ission PDF, Multi page f plder, USB, SD Card, UI 1 Standard paper tray(s Optional paper tray(s	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages) 3): SRA3, A3, A4, A5, A6, B4 (4, A5, A6, B4, B5, B6, Enve 1,200 sheets 4,700 sheets 500 sheets	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes	°STN, PBX 81 spm
4500LT) anning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX rcuit ansmission speed oddem speed: maximum esolution: standard esolution: option pmpression method canning speed emory: standard emory: standard emory: maximum APER HANDLING ecommended paper size aper input: standard aper input: standard aper output: standard	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page tit page TIFF, Multi page ission PDF, Multi page F plder, USB, SD Card, UI Standard paper tray(s Optional paper tray(s pass tray: SRA3, A3, A	e High compression PDF, PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages) 5): SRA3, A3, A4, A5, A6, B4 (A, A5, A6, B4, B5, B6, Enve 1,200 sheets 4,700 sheets 500 sheets 3,625 sheets	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes lopes, Custom Size pape	°STN, PBX 81 spm
4500LT) canning speed: SPDF (IM 5500ALT, IM C6000LT) esolution: maximum le formats can modes AX AX AX AX AX AX AX AX AX AX	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page tit page TIFF, Multi page ission PDF, Multi page F plder, USB, SD Card, UI Standard paper tray(s Optional paper tray(s pass tray: SRA3, A3, A	e High compression PDF, e PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages) 3): SRA3, A3, A4, A5, A6, B4 (4, A5, A6, B4, B5, B6, Enve 1,200 sheets 4,700 sheets 500 sheets	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes lopes, Custom Size pape	°STN, PBX 81 spm
4500LT) anning speed: SPDF (IM 5500LT, IM C600LT) esolution: maximum le formats can modes AX	Single Page TIFF, Single p Single page PDF/A, Mul compre E-mail, Fo PSTN, PBX	120 ipm (simplex) 1,200 dpi page JPEG, Single page tit page TIFF, Multi page ission PDF, Multi page f plder, USB, SD Card, UI Standard paper tray(s Optional paper tray(s rpass tray: SRA3, A3, A Trays: (60 - 300 g/m²),	e High compression PDF, PDF, Multi page High PDF/A RL, FTP PSTN, PBX 2 seconds 33.6 Kbps 3x3.85 line/mm, 200x100 dp 6x15.4 line/mm, 400x400 dp MH, MR, MMR, JBIG 81 spm 4 MB, (320 pages) 60 MB, (4,800 pages) 60 MB, (4,800 pages) 5): SRA3, A3, A4, A5, A6, B4 (A, A5, A6, B4, B5, B6, Enve 1,200 sheets 4,700 sheets 500 sheets 3,625 sheets	F i i 4, B5, B6, Envelopes 4, B5, B6, Envelopes lopes, Custom Size pape	ISTN, PBX

## RICOH IM C4500LT/ IM C5500ALT/ IM C6000LT

MAIN SPECIFICATIONS

	IM C4500LT	IM C5500ALT	IM C6000LT	
ECOLOGY				
Power consumption: max.		Less than 1,850 W		<b>S</b>
Power consumption operation: B&W	644.6 W	821.7 W	837.7 W	Adobe" PostScript" 3"
Power consumption operation: Full colour	729.9 W	935.4 W	957 W	🚷 Bluetooth
Power consumption: ready		59 W		
Power consumption: sleep		0.62 W		
TEC* * It is a reference value based on the ENERGY STAR Ver.3.0 test	0.52 kWh/week	0.71 kWh/week	0.76 kWb/week	Wifi certified

TAR Ver.3.0 test method.

### OUTPUT TRAYS AND FINISHER OPTIONS

1x 550-sheet paper tray	Paper size: (SRA3, A3, A4, A5, A6, B4, B5, B6), Paper weight: (60-300 g/m <sup>2</sup> )
2x 550-sheet paper tray	Paper size: (SRA3, A3, A4, A5, A6, B4, B5, B6), Paper weight: (60-300 g/m <sup>2</sup> )
2,000-sheet Large capacity tray	Paper size: (A4), Paper weight: (60-300 g/m <sup>2</sup> )
1,500-sheet side Large capacity tray	Paper size: (A4, B5), Paper weight: (60-300 g/m <sup>2</sup> )
1,000-sheet Hybrid finisher	Paper size: (SRA3, A3, A4, A5, A6, B4, B5, B6), Paper weight: (52-300 g/m <sup>2</sup> ), Stack capacity: (1,000 sheets), Staple capacity: (50 sheets), Staple paper size: (A3, A4, B4, B5), Staple paper weight: (52-105 g/m <sup>2</sup> ), Staple positions: (Top, Bottom, 2 Staples)
3,000-sheet finisher	Paper size: (SRA3, A3, A4, A5, A6, B4, B5, B6), Paper weight: (52-300 g/m <sup>2</sup> ), Stack capacity: (3,000 sheets), Staple capacity: (50 sheets), Staple paper size: (A3, A4, B4, B5), Staple paper weight: (52-105 g/m <sup>2</sup> ), Staple positions: (Top, Bottom, 2 staples, Top-slant)
1,000-sheet Booklet finisher	Paper size: (SRA3, A3, A4, A5, A6, B4, B5, B6), Paper weight: (52-300 g/m <sup>2</sup> ), Stack capacity: (1,000 sheets), Staple capacity: (50 sheets), Staple paper size: (A3, A4, B4, B5), Staple paper weight: (52-105 g/m <sup>2</sup> ), Staple positions: (Top, Bottom, 2 staples, Booklet)
2,000-sheet Booklet finisher	Paper size: (SRA3, A3, A4, A5, A6, B4, B5, B6), Paper weight: (52-300 g/m <sup>2</sup> ), Stack capacity: (2,000 sheets), Staple capacity: (50 sheets), Staple paper size: (A3, A4, B4, B5), Staple paper weight: (52-105 g/m <sup>2</sup> ), Staple positions: (Top, Bottom, 2 staples, Booklet)
500-sheet Internal finisher	Paper size: (A3, A4, A5, A6, B4, B5), Paper weight: (52-300 g/m²), Stack capacity: (500 sheets), Staple capacity: (50 sheets), Staple paper size: (A3, A4, B4, B5), Staple paper weight: (52-105 g/m²), Staple positions: (Top, Bottom, 2 staples)
Internal shift tray	Tray capacity: (250 sheets), Paper size: (SRA3, A3, A4, A5, A6, B4, B5, B6), Paper weight: (52-300 g/m²)
One-bin tray	Tray capacity: (125 sheets), Paper size: (A3, A4, A5, B4), Paper weight: (52-300 g/m <sup>2</sup> )

### OTHER OPTIONS

Fax unit, G3 Interface, Fax connection unit, Fax memory unit, Cabinet, Caster table, VM card, Memory unit, Side Tray, Banner paper guide tray, Punch units, Internal Multi-fold unit, IPDS unit, Camera direct print card, PostScript 3, Bi-directional IEEE 1284, IEEE 802.11 a/g/n, Device server unit, File format converter, OCR unit, Enhanced security HDD, Data overwrite security unit, Small paper feeding unit, Page keeper, Imageable area extension unit, ADF handle, External keyboard bracket, Counter I/F unit, Key counter bracket, NFC card reader, Smart card reader built-in unit, EFI controller, EFI Impose, EFI Compose, EFI Hot folders, EFI Spot on

#### CONSUMABLES

Toner (black) Toner: cyan/magenta/yellow Consumable yield based on 4p/j 5% coverage on A4

33,000 prints 22,500 prints



# www.stanfordmarsh.co.uk info@stanfordmarsh.co.uk | 0844 856 0701



COMMISSION REGULATION (EU) 2019/2020. The light source of this product is not intended for applications other than image printing.



The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2022 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.





RICOH @Remote